



contractor SOLUTIONS

MSF

MID SOLIDS FINISH PISO ACABADO CON SÓLIDOS MEDIO



MSF MID SOLIDS FINISH has been specifically formulated for high initial gloss and "wet look" response to burnishing. Due to MSF's outstanding durability to high traffic conditions, it is the recommended finish for retail stores (to include supermarkets, department stores, shopping malls), airports and schools.

MSF is easily maintained with less effort due to its ability to repel heel marks and soil. Its tough film does not allow dirt penetration, yet will respond to daily burnishing for that "wet-look" appearance.

Recommended for use on vinyl asbestos, vinyl, reinforced vinyl, asphalt and other types of resilient floors as well as non-resilient terrazzo floors.

| Features | - Related Benefits |
|--|---|
| Excellent gloss | - Provides wet-look finish |
| Average solids | - Easy to apply |
| Excellent slip resistance | - Reduces liability potential |
| Polymer formula | - Durable and chemical resistant |
| Use with any speed buffer or burnisher | - Excellent for any maintenance program |
| Removes with finish dissolving strippers | - Easy to remove |

Areas of Use -

Use on resilient tile floors, concrete, terrazzo, and other floor surfaces in:

- Restaurants, hotels, motels, offices
- Hospitals, nursing homes, doctors offices
- Schools, universities, child care centers
- Grocery stores, malls, retail stores

To Use -

Completely strip off all old floor finish. Apply finish in thin to medium coats. It is recommended that a minimum of 4 to 5 coats of MSF be applied after floor has been stripped. **For applications, see label for complete directions and use only as directed.**

Specification Data

| | |
|-----------------------------|--------------------------------|
| Available Sizes - 4/1G, 5G | Physical State - Liquid |
| Color - Milky white | Fragrance - Acrylic |
| Total solids - 15% | Metal Interlocked - Yes |
| Initial Gloss - Excellent | Traffic Area - Normal |
| Slip Resistance - Excellent | Burnisher Response - Excellent |
| pH - 8.3-8.9 | DOT - Not regulated |
| VOCs - <1% | |

Rev. 0109 1TS9925A55

Manufactured by
CARROLL COMPANY
Garland, TX 75041
Havre de Grace, MD 21078
Sante Fe Springs, CA 90670
800.527.5722
www.carrollco.com